

## Electric Series Scissor Lifts

# 0407SE(1330SE)/0607SE(1932SE)

Compliance with GB/CE/AS/EAC/ANSI/CSA standards

### Product Highlights

- Platform capacity up to 240kg(529lbs)
- Easily passes through standard doors and can access elevators
- Exclusive open chassis reduces daily maintenance time
- DC motor drive, giving a longer runtime

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Full-stroke operation
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4×2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

# SINOBOOM

Sinoboom Intelligent Equipment

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,  
Changsha, Hunan, China, 410600

🌐 [www.sinoboom.com](http://www.sinoboom.com)

✉ [sales@sinoboom.com](mailto:sales@sinoboom.com)

## Electric Series Scissor Lifts

# 0407SE(1330SE)/0607SE(1932SE)

Compliance with GB/CE/AS/EAC/ANSI/CSA standards

# SINOBOOM

Model		0407SE(1330SE)	0607SE(1932SE)
<b>Dimension</b>			
Max Working Height		5.8m(19')	7.6m(24'11")indoor 6.6m(21'26")outdoor
A	Max Platform Height	3.8m(12'6")	5.6m(18'5") indoor 4.6m(15')outdoor
B	Max Horizontal Extension	0.6m(23.6")	0.6m(23.6")
C	Length-Stowed	1.42m(4'8")	1.52m(4'12")
D	Width-Stowed	0.76m(2'6")	0.81m(2'8")
Height - stowed	Rail Folded	1.67m(6'5")	1.77m(5'10")
	E Rail Unfolded	1.97m(6'6")	2.1m(6'11")
	Fixed Rail	1.97m(6'6")	2.1m(6'11")
F	Wheelbase	1.11m(3'8")	1.13m(3'9")
Ground Clearance(Pothole Guard Stowed)		0.065m(2.6")	0.065m(2.6")
Ground Clearance(Pothole Guard Deployed)		0.02m(0.75")	0.025m(0.98")
Platform Dimensions(L×W×H)		1.34m×0.7m×1.1m(4'4"×2'4"×3'7")	1.37m×0.7m×1.1m(4'6"×2'4"×3'7")
<b>Performance</b>			
Platform Allowable Occupants(Indoor)		2 persons(indoor)	2 persons(indoor) 1person(outdoor)
Platform capacity		240kg(529lbs)	230kg(507lbs)
Lift Extension Capacity		100kg(220lbs)	120kg(265lbs)
Drive Speed-Stowed		4km/h(2.5mph)	4km/h(2.5mph)
Drive Speed-Raised		0.8km/h(0.5mph)	0.8km/h(0.5mph)
Lift Time(Unloaded)		30s~33s	26s
Descent Time(Unloaded)		25s~30s	24s
Gradeability		25%	25%
Turning Radius(Inside/Outside)		0.3m/1.35m(12"/4'5")	0.45m/1.6m(18"/5'3")
Tilt Rating(Front to Back/Side to Side)		3°/1.5°	3°/1.5°
Tyre Size/Type		230×80mm (9×3")/solid	255×80mm (10×3.2")/solid
<b>Power</b>			
Batteries		12V×2/115Ah	12V×2/115Ah
Power Source		24V DC	24V DC
Drive Mode		Motor, Rear wheel	Motor, Front wheel
Charger Input		100~240V AC	100~240V AC
Charger Output		15A	15A
Hydraulic System Capacity		5L(1.1gal)(UK)/1.325 gal(US))	4 L (0.9 gal(UK)/1.05 gal(US))
<b>Weight</b>			
Weight(Indoor)		880kg(1,940lbs)	1,210kg(2,668lbs)
Standards Compliance		GB/CE/AS/EAC/ANSI/CSA	

