

METEOR 350

SPECIFICATIONS



FRAME

Frame type Twin Downtube Spine Frame

DIMENSIONS

Weight in running order (Kg.) 191
 Wheelbase (mm) 1400
 Seat height (mm) 765
 Ground clearance (mm) 170
 Length x width x height (mm)
 (without mirrors & without
 windshield) 2140 x 845 x 1140

ENGINE

Number of cylinders 1
 Bore x stroke (mm) 72x85.8
 Cooling System Air-Oil Cooled
 Displacement (cc) 349
 Injection system ECU controlled
 Valve gear / valves per cylinder 2
 Compression ratio 9.5:1
 Maximum power (kw/bhp-rpm) 14.87kW@6100 rpm
 Maximum speed 114 km/h (4th Gear) (70.8 mph)
 Maximum torque (Nm @ rpm) 27Nm@4000 rpm
 CO2 emission (g/km) 67.25 g/km
 Idle rpm 1050 ± 100
 Noise Emission (dB-(A) - rpm) 89.0 dB(A) @ 3050 rpm
 Clutch Conventional Wet Clutch
 Secondary transmission Chain
 Gearbox 5 Speed Constant Mesh
 Starting System Electric
 Engine Oil SAE 15W50 API SL Jaso MA2
 Semi-synthetic

CHASSIS AND BRAKES

Front wheel Tyre 100/90-19 M/C 57P
 (For After Market replacemnt - 100/90-19
 M/C 57V - Metzler)
 Rear wheel Tyre 140/70-17 M/C 66P
 (For After Market replacemnt 140/70-17
 M/C 66H - Metzler)
 Front suspension Telescopic 41 mm Forks, 130mm Travel
 Rear suspension Twin Tube Emulsion shock absorber with
 6 step adjustable preload
 ABS Dual Channel
 Front brake 300mm disc with twin piston floating caliper
 Rear brake 270mm disc, single piston floating caliper

CAPACITY

Petrol tank (imperial gallons) 3.3 ± 0.11
 Low fuel warning 1.1 ± 0.11
 Consumption (2.79 L/100 km)

EQUIPMENT

Instrument Cluster Digital LCD with analog speedometer
 Navigation Model god 24 -Tripper standard fit
 *model prethodnih godina - Tripper dostupan
 Engine Kill Switch Yes
 Far 12V, 14/12W (LED) - LED far standardni fit
 samo na modelu Aurora i Supernova.
 Central and side stand Fabricated and Spring loaded
 Engine Guard
 Tool kit Provided in Right side cabinet of vehicle
 Side stand switch Yes
 Luggage rack

COLOURS

