

## ICON CT30D (TRP) TECHNICAL SPECIFICATIONS

	DEFINITION	UNIT	ICON CT30D
Identification	Producer		Ceytech Makina San.Ve Tic.A.Ş.
	Origin		Türkiye
	Power Type		Diesel
	Load Capacity/ Rated Load	kg	3000
	Load Center Distance	c mm	500
	Load distance, center of drive axle to fork	x mm	580
	Wheelbase	y mm	1750
Weights	Service Weight	kg	4800
	Axle loading, loaded front/rear	Kg	6730 / 1070
	Axle loading, unloaded front/rear	Kg	1845 / 2955
Wheels, Chassis	Tires: solid rubber (V), pneumatic (P), süper elastic (SE),polyurethane(PE)		P
	Tires size front		28x9x15-12 PR
	Tires size rear		6.50-10-10 PR
	Wheels number front, rear (x= driven wheels)		2 / 2
	Tread, front/rear	mm	1040 / 1020
Basic Dimintions	Mast/fork carriage tilt forward/backward	degrees	5°/11°
	Lowered mast height	h1 mm	2200
	Free Lift	h2 mm	1600
	Lifting Height	h3 mm	4700
	Extended Mast Height	h4 mm	5800
	Overhead load guard (cab) height	h5 mm	2130
	Overall Length	i1 mm	4000
	Length to face of forks	i2 mm	2780
	Overall Width	b1 mm	1245
	Fork Dimintions	TxWxL mm	45 x125 x 1220
	Fork Carriage Class, ISO2328 type A,B		3A
	Fork Carriage Width	b2 mm	1100
	Ground clearance, loaded, under mast	m1 mm	145
	Ground clearance, centre of wheelbase	m2 mm	130
	Aisle width for pallets 1000 x 1200 crossways	AST mm	4390
Turning Radius	Wa mm	2400	
Performance Data	Travel Speed, loaded/unloaded	Km /h	18/20
	Lifting Speed, loaded/unloaded	mm / h	325/375
	Lowering Speed, loaded/unloaded	mm /h	370/335
	Max Slope Performance ( s2 5min) loaded	%	25
	Service Brake		Hydraulic
	Parking Brake		Mechanic
	Steering Wheel, Type		Hydraulic
	Battery, Voltage/Capacity	V/Ah	12/90
Engine	Engine		Zhejiang Xinchai
	Model		3E22YG51
	Nominal Output SAE net	HP/kW	63/44,8
	Nominal Turnover	Min-1	2520
	Max.Torque SAE net	Nm@min-1	210
Other Details	Drive Control Type		Automatic Transmission
	Fuel Tank Capacity	L	75
	Attachment's pressure	bar	180



## ICON CT35D (TRP) TECHNICAL SPECIFICATIONS

	DEFINITION	UNIT	ICON CT35D
Identification	Producer		Ceytech Makina San.Ve Tic.A.Ş.
	Origin		Türkiye
	Power Type		Diesel
	Load Capacity/ Rated Load	kg	3500
	Load Center Distance	c mm	500
	Load distance, center of drive axle to fork	x mm	580
	Wheelbase	y mm	1750
Weights	Service Weight	kg	4935
	Axle loading, loaded front/rear	Kg	7135 / 1300
	Axle loading, unloaded front/rear	Kg	1905 / 3030
Wheels, Chassis	Tires: solid rubber (V), pneumatic (P), süper elastic (SE),polyurethane(PE)		P
	Tires size front		28x9x15-12 PR
	Tires size rear		6.50-10-10 PR
	Wheels number front, rear (x= driven wheels)		2 / 2
	Tread, front/rear	mm	1040 / 1020
Basic Dimentions	Mast/fork carriage tilt forward/backward	degrees	5°/11°
	Lowered mast height	h1 mm	2200
	Free Lift	h2 mm	1600
	Lifting Height	h3 mm	4700
	Extended Mast Height	h4 mm	5800
	Overhead load guard (cab) height	h5 mm	2130
	Overall Length	i1 mm	4000
	Length to face of forks	i2 mm	2780
	Overall Width	b1 mm	1245
	Fork Dimentions	TxWxL mm	45 x125 x 1220
	Fork Carriage Class, ISO2328 type A,B		3A
	Fork Carriage Width	b2 mm	1100
	Ground clearance, loaded, under mast	m1 mm	145
	Ground clearance, centre of wheelbase	m2 mm	130
	Aisle width for pallets 1000 x 1200 crossways	AST mm	4390
	Turning Radius	Wa mm	2400
Performance Data	Travel Speed, loaded/unloaded	Km /h	17/20
	Lifting Speed, loaded/unloaded	mm / h	325/375
	Lowering Speed, loaded/unloaded	mm /h	370/335
	Max Slope Performance ( s2 5min) loaded	%	25
	Service Brake		Hydraulic
	Parking Brake		Mechanic
	Steering Wheel, Type		Hydraulic
	Battery, Voltage/Capacity	V/Ah	12/90
Engine	Engine		Zhejiang Xinchai
	Model		3E22YG51
	Nominal Output SAE net	HP/kW	63/44,8
	Nominal Turnover	Min-1	2520
	Max.Torque SAE net	Nm@min-1	210
Other Details	Drive Control Type		Automatic Transmission
	Fuel Tank Capacity	L	75
	Attachment's pressure	bar	180

